

**Editor Contact:** Sarah Beck, (512) 683-5126  
**Reader Contact:** Ernest Martinez, (800) 258-7022

## **National Instruments Introduces NI Single-Board RIO Embedded Devices With Multifunction I/O for Custom Application Development**

### **News Highlights**

- Multifunction I/O in a board-level reconfigurable I/O (RIO) product with built-in analog I/O
- Customization through daughter cards on two models
- More built-in peripherals including two RS232 serial ports, an RS485 port, Ethernet and options for a CAN port, USB port and SDHC card slot
- Alleviates the effort of designing an entire embedded system from scratch so designers can focus on the custom parts of their applications

**NUREMBERG, Germany – Embedded World – Feb. 28, 2012** – National Instruments (Nasdaq: NATI) today announced four new [NI Single-Board RIO](#) board-level embedded devices featuring a real-time processor, Spartan-6 field-programmable gate array (FPGA), analog and digital I/O and more built-in peripherals for custom embedded control and monitoring applications. The new devices provide engineers with off-the-shelf FPGA and real-time processor technology through [NI LabVIEW](#) while maintaining the custom I/O often required for high-volume deployments through the option of a RIO Mezzanine Card connector. The connector provides direct access to FPGA digital input/output (DIO) lines and certain processor-specific functions for mating custom daughter cards. NI Single-Board RIO alleviates the effort of designing an entire system from scratch so designers can focus on the custom parts of their applications, such as the I/O.

With the new devices, engineers can achieve the shorter time to market of an off-the-shelf system along with the I/O customization offered by in-house designs, providing the best of both worlds. The devices also feature built-in analog I/O so engineers can take advantage of the company's industry-leading analog expertise in addition to their application-specific circuitry. The devices' low-cost, small form factor; built-in I/O; real-time processor; and FPGA provide an ideal platform for embedded monitoring and control applications in industries such as medical and energy.

### **Product Features**

- *NI sbRIO-9623*: 256 MB of memory, 128 MB RAM, 16 channels of 12-bit analog input, 4 channels of 12-bit analog output, 4 DIO, 96 RMC DIO

- *NI sbRIO-9626*: 512 MB of memory, 256 MB RAM, 16 channels of 16-bit analog input, 4 channels of 16-bit analog output, 4 DIO, 96 RMC DIO
- *NI sbRIO-9633*: 256 MB of memory, 128 MB RAM, 16 channels of 12-bit analog input, 4 channels of 12-bit analog output, 28 DIO
- *NI sbRIO-9636*: 512 MB of memory, 256 MB RAM, 16 channels of 16-bit analog input, 4 channels of 16-bit analog output, 28 DIO

**Learn more by viewing these additional resources:**

- **Product:** [See What's New With NI Single-Board RIO](#)
- **Video:** [NI Single-Board RIO Out of the Box](#)

**Click to Tweet:** From #EW2012, @NIGlobal releases 4 new NI Single-Board RIO embedded devices that offer multifunction I/O for custom design *[\[insert bit.ly link\]](#)*

## About NI RIO

NI reconfigurable I/O (RIO) hardware combined with NI LabVIEW system design software provides a commercial off-the-shelf solution to simplify development and shorten time to market when designing advanced control, monitoring and test systems. NI RIO hardware, which includes CompactRIO, NI Single-Board RIO, R Series devices and PXI-based NI FlexRIO, features an architecture with powerful floating-point processors, reconfigurable FPGAs and modular I/O. Engineers can program all NI RIO hardware components with NI LabVIEW to rapidly create custom timing, signal processing and control for I/O without requiring expertise in low-level hardware description languages or board-level design.

## About National Instruments

Since 1976, National Instruments ([www.ni.com](http://www.ni.com)) has equipped engineers and scientists with tools that accelerate productivity, innovation and discovery. NI's graphical system design approach to engineering provides an integrated software and hardware platform that speeds the development of any system needing measurement and control. The company's long-term vision and focus on improving society through its technology supports the success of its customers, employees, suppliers and shareholders.

## Pricing and Contact Information

NI sbRIO-96xx

11500 N Mopac Expwy, Austin, Texas 78759-3504

Contact NI for pricing information

Web: [www.ni.com/singleboard](http://www.ni.com/singleboard)

*\*All prices are subject to change without notice.*

Tel: (800) 258-7022, Fax: (512) 683-9300

Email: [info@ni.com](mailto:info@ni.com)

*CompactRIO, LabVIEW, National Instruments, NI, ni.com and NI FlexRIO are trademarks of National Instruments. Other product and company names listed are trademarks or trade names of their respective companies.*

###