

SPECIFICATIONS

USB-6501

24-Channel, 8.5 mA, Digital I/O Device

Definitions

Warranted specifications describe the performance of a model under stated operating conditions and are covered by the model warranty.

The following characteristic specifications describe values that are relevant to the use of the model under stated operating conditions but are not covered by the model warranty.

- *Typical* specifications describe the performance met by a majority of models.
- *Nominal* specifications describe an attribute that is based on design, conformance testing, or supplemental testing.

Specifications are *Typical* unless otherwise noted.

Conditions

Specifications are valid at 25 °C unless otherwise noted. All voltages are relative to COM unless otherwise noted.

Digital I/O

Number of lines

P0.<0..7>	8
-----------	---

P1.<0..7>	8
-----------	---

P2.<0..7>	8
-----------	---

Direction control	Input or output, software-selectable
-------------------	--------------------------------------

Output driver type	Active drive (push-pull) or open collector (open-drain), software selectable
--------------------	--

Pull-up resistor	4.7 k Ω Vbus (nominally 5 V)
------------------	-------------------------------------

Absolute voltage range	-0.5 V to 5.8 V with respect to GND
------------------------	-------------------------------------

Power-on state	Input (high impedance)
----------------	------------------------

Digital Logic Levels

Input low voltage	-0.3 V minimum, 0.8 V maximum
Input high voltage	2.0 V minimum, 5.8 V maximum
Input leakage current	50.0 μ A maximum
Output low voltage, open collector or active drive	
$I_{OL} = 2$ mA	0.4 V maximum
$I_{OL} = 8.5$ mA	0.8 V maximum
Output high voltage, active drive ¹	
$I_{OH} = -2$ mA	2.8 V minimum, 3.6 V maximum
$I_{OH} = -8.5$ mA	2.0 V minimum, 3.5 V maximum
Output high voltage, open collector	
$I_{OH} = -0.4$ mA, nominal	2.0 V minimum, 5.0 V maximum
$I_{OH} = -7.5$ mA, with external pull-up resistor	2.0 V minimum

Counter

Number of counters	1 (P2.7 can be configured as a counter)
Resolution	32 bits
Counter measurements	Falling edge counting
Maximum input frequency	5 MHz
Minimum high pulse width	100 ns
Minimum low pulse width	100 ns

Bus Interface

USB specification	USB 2.0 Full Speed (12 Mb/s)
-------------------	------------------------------

¹ The total current sourced by all DO lines simultaneously should not exceed 65 mA.

External Voltage

+5 V output

Voltage	4.00 V minimum, 5.25 V maximum
Current	230 mA maximum

Power Requirements

USB

Input voltage	4.50 VDC to 5.25 VDC, in configured state
Active current	80 mA typical, 500 mA maximum
Suspend current	500 μ A maximum, all DIO lines disconnected

Physical Characteristics

Dimensions

Without connectors	6.35 cm \times 8.51 cm \times 2.31 cm (2.50 in. \times 3.35 in. \times 0.91 in.)
With connectors	8.18 cm \times 8.51 cm \times 2.31 cm (3.22 in. \times 3.35 in. \times 0.91 in.)


Weight	84 g (3 oz)
--------	-------------

USB connector	USB series B receptacle (1)
---------------	-----------------------------

I/O connectors

Type	16-position (screw terminal) plug headers (2)
Screw terminal wiring	16 AWG to 28 AWG copper conductor wire with 10 mm (0.39 in.) of insulation stripped from the end
Torque for screw terminals	0.22 N \cdot m to 0.25 N \cdot m (2.0 lb \cdot in. to 2.2 lb \cdot in.)

Figure 1. USB-6501 Dimensions



If you need to clean the module, wipe it with a dry towel.

Safety Voltages

Connect only voltages that are within these limits.

Channel-to-COM (one channel)	±30 V max, Measurement Category I
Channels-to-COM (one port, all channels)	±8.9 V max, Measurement Category I

Measurement Category I is for measurements performed on circuits not directly connected to the electrical distribution system referred to as MAINS voltage. MAINS is a hazardous live electrical supply system that powers equipment. This category is for measurements of voltages from specially protected secondary circuits. Such voltage measurements include signal levels, special equipment, limited-energy parts of equipment, circuits powered by regulated low-voltage sources, and electronics



Caution Do not use this module for connection to signals or for measurements within Measurement Categories II, III, or IV



Note Measurement Categories CAT I and CAT O (Other) are equivalent. These test and measurement circuits are not intended for direct connection to the MAINS building installations of Measurement Categories CAT II, CAT III, or CAT IV.

Environmental

Temperature (IEC 60068-2-1 and IEC 60068-2-2)

Operating	0 °C to 55 °C
Storage	-40 °C to 85 °C

Humidity (IEC 60068-2-56)

Operating	5% to 90% RH, noncondensing
Storage	5% to 90% RH, noncondensing

Pollution Degree (IEC 60664)

2

Maximum altitude

2,000 m

Indoor use only.

Hazardous Locations

This device is not certified for use in hazardous locations.

Safety

This product is designed to meet the requirements of the following electrical equipment safety standards for measurement, control, and laboratory use:

- IEC 61010-1, EN 61010-1
- UL 61010-1, CSA C22.2 No. 61010-1



Note For UL and other safety certifications, refer to the product label or the [Online Product Certification](#) section.

Electromagnetic Compatibility

This product meets the requirements of the following EMC standards for electrical equipment for measurement, control, and laboratory use:

- EN 61326-1 (IEC 61326-1): Class A emissions; Basic immunity
- EN 55011 (CISPR 11): Group 1, Class A emissions
- EN 55022 (CISPR 22): Class A emissions
- EN 55024 (CISPR 24): Immunity
- AS/NZS CISPR 11: Group 1, Class A emissions
- AS/NZS CISPR 22: Class A emissions

- FCC 47 CFR Part 15B: Class A emissions
- ICES-001: Class A emissions



Note In the United States (per FCC 47 CFR), Class A equipment is intended for use in commercial, light-industrial, and heavy-industrial locations. In Europe, Canada, Australia and New Zealand (per CISPR 11) Class A equipment is intended for use only in heavy-industrial locations.



Note Group 1 equipment (per CISPR 11) is any industrial, scientific, or medical equipment that does not intentionally generate radio frequency energy for the treatment of material or inspection/analysis purposes.



Note For EMC declarations and certifications, and additional information, refer to the [Online Product Certification](#) section.

CE Compliance

This product meets the essential requirements of applicable European Directives as follows:

- 2006/95/EC; Low-Voltage Directive (safety)
- 2004/108/EC; Electromagnetic Compatibility Directive (EMC)

Online Product Certification

Refer to the product Declaration of Conformity (DoC) for additional regulatory compliance information. To obtain product certifications and the DoC for this product, visit ni.com/certification, search by model number or product line, and click the appropriate link in the Certification column.

Environmental Management

NI is committed to designing and manufacturing products in an environmentally responsible manner. NI recognizes that eliminating certain hazardous substances from our products is beneficial to the environment and to NI customers.

For additional environmental information, refer to the *Minimize Our Environmental Impact* web page at ni.com/environment. This page contains the environmental regulations and directives with which NI complies, as well as other environmental information not included in this document.

Waste Electrical and Electronic Equipment (WEEE)



EU Customers At the end of the product life cycle, all NI products must be disposed of according to local laws and regulations. For more information about how to recycle NI products in your region, visit ni.com/environment/weee.

电子信息产品污染控制管理办法（中国 RoHS）



中国客户 National Instruments 符合中国电子信息产品中限制使用某些有害物质指令 (RoHS)。关于 National Instruments 中国 RoHS 合规性信息，请登录 ni.com/environment/rohs_china。(For information about China RoHS compliance, go to ni.com/environment/rohs_china.)

Information is subject to change without notice. Refer to the *NI Trademarks and Logo Guidelines* at ni.com/trademarks for information on NI trademarks. Other product and company names mentioned herein are trademarks or trade names of their respective companies. For patents covering NI products/technology, refer to the appropriate location: **Help»Patents** in your software, the `patents.txt` file on your media, or the *National Instruments Patent Notice* at ni.com/patents. You can find information about end-user license agreements (EULAs) and third-party legal notices in the `readme` file for your NI product. Refer to the *Export Compliance Information* at ni.com/legal/export-compliance for the NI global trade compliance policy and how to obtain relevant HTS codes, ECCNs, and other import/export data. NI MAKES NO EXPRESS OR IMPLIED WARRANTIES AS TO THE ACCURACY OF THE INFORMATION CONTAINED HEREIN AND SHALL NOT BE LIABLE FOR ANY ERRORS. U.S. Government Customers: The data contained in this manual was developed at private expense and is subject to the applicable limited rights and restricted data rights as set forth in FAR 52.227-14, DFAR 252.227-7014, and DFAR 252.227-7015.

© 2015—2017 National Instruments. All rights reserved.

375268C-01 September 22, 2017